

**ORBEA**



## OIZ M-LTD.

ESTÁ EN ESTOS COLORES:



AZUL INDIGO-BRIGHT RED  
(MATE)



MENTA-NEGRO (BRILLO)



NARANJA-GRAFITO (MATE)



GRAFITO (BRILLO) / NEGRO  
(MATE)

## ESPECIFICACIONES Y OPCIONES

<b>CUADRO</b>	Orbea Oiz Carbon OMR FiberLink Boost PF Taper UFO2 I-Line
<b>AMORTIGUADOR</b>	Fox i-line DPS Factory 100mm Remote Push-Unlock Evol Kashima custom tune190x40mm
<b>HORQUILLA</b>	Fox 32 Float SC Factory 100 FIT4 Remote-Adj Push-Unlock QR15x110 Kashima
<b>PLATO</b>	SRAM XX1 Eagle Dub Grey Boost 34t
<b>DIRECCION</b>	Acros Alloy 1-1/8 - 1-1/2" Integrated
<b>MANILLAR</b>	FSA K-Force Flat 760mm Di2 compatible
<b>POTENCIA</b>	FSA K-Force
<b>MANETAS</b>	SRAM XX1 Eagle AXS
<b>FRENO</b>	SRAM Ultimate Carbon Stealth-a-majig Black Hydraulic Disc
	Shimano XTR M9100 Hydraulic Disc
<b>PIÑON</b>	SRAM XX1 XG-1299 Eagle 10-50t 12-Speed Rainbow
<b>CAMBIO</b>	SRAM XX1 Eagle AXS
<b>CADENA</b>	SRAM XX1 Eagle 12-Speed rainbow
<b>RUEDA</b>	DT Swiss XRC-1200 Spline 25c TLR 15/110mm CL
<b>CUBIERTA</b>	Maxxis Ikon 2.20" FB 120 TPI 3C Exo TR
<b>CUBIERTA</b>	Maxxis Ardent 2.2" FB Dual Exo TR
<b>PEDALES</b>	N/A
<b>TIJA SILLIN</b>	FSA K-Force Light SB0 31.6x400mm Di2 compatible
	OC2 Dropper 31.6mm 125mm travel
	OC2 Dropper 31.6mm 150mm travel
<b>SILLIN</b>	Selle Italia X-LR Kit Carbonio L
<b>BATERÍA</b>	SRAM Powerpack
<b>EJE RUEDA DELANTERO</b>	
<b>BLOQUEO REMOTO</b>	OC Squidlock 3-position
--	

## GEOMETRÍA

TALLA	S-27.5"-XC	S-29"-XC	M-29"-XC	L-29"-XC	XL-29"-XC	-	S-27.5"-TR	S-29"-TR	M-29"-TR	L-29"-TR	XL-29"-TR
<b>1 - SEAT_TUBE</b>	405	405	432	470	520	-	405	405	432	470	520
<b>2 - TOP_TUBE</b>	557	564	593	617	641	-	559	567	596	619	643
<b>3 - HEAD_TUBE</b>	95	90	95	105	120	-	95	90	95	105	120
<b>4 - CHAIN_STAY</b>	425	435	435	435	435	-	425	435	435	435	435
<b>5 - BB_HEIGHT</b>	328	327	327	327	327	-	336	334	334	334	334
<b>6 - BB_DROP</b>	29	47	47	47	47	-	21	40	40	40	40
<b>7 - WHEELBASE</b>	1081	1094	1123	1148	1173	-	1088	1101	1131	1155	1181
<b>8 - HEAD_ANGLE</b>	69º	69º	69º	69º	69º	-	68º	68º	68º	68º	68º
<b>9 - SEAT_ANGLE</b>	75º	75º	75º	75º	75º	-	74º	74º	74º	74º	74º
<b>10 - STANDOVER</b>	715	717	732	742	749	-	722	724	739	749	756
<b>11 - REACH</b>	407	407	435	456	476	-	397	387	425	446	466
<b>12 - STACK</b>	558	586	591	600	614	-	565	593	598	608	622
<b>13 - FORK_LENGTH</b>	488	504	504	504	504	-	508	524	524	524	524
<b>14 - OFFSET</b>	44	44	44	44	44	-	44	44	44	44	44

## ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR
<b>S-27</b>	170	60	760
<b>S-29</b>	170	60	760
<b>M-29</b>	175	70	760
<b>L-29</b>	175	70	760
<b>XL-29</b>	175	90	760

\* La medida del manillar es centro-centro

